

P-400

125 kHz Proximity Card Reader

Pyramid Series Proximity®
Data Sheet



Application - Vandal resistant design makes it ideal for applications such as door access (mullion, door or window frame mount), gate entry and parking barriers.

Compatible - Wiegand and magnetic stripe protocols for easy integration with standard access systems.

Industry Friendly - Can support several proximity card and tag technologies.

Performance - Delivers non-contact read ranges up to 1 inch (25 mm).

Durable - Electronics are secured with tamper- and weather-resistant epoxy potting, and backed by a lifetime warranty.

Pyramid Series Proximity from Farpointe Data sets the electronic security benchmark for 125 kHz proximity readers, card and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

©2012 Farpointe Data, Inc. All rights reserved. Farpointe Data, the Farpointe Data logo, Pyramid Series Proximity, Pyramid Series logo, Ranger and Delta are registered trademarks of Farpointe Data, Inc. Mifare is a registered trademark of NXP Semiconductors. AWID is a trademark of Applied Wireless Identifications Group. HID and the HID logo are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

260 North Wolfe Road
Sunnyvale, CA 94085 USA
Tel: +1-408-731-8700
Email: support@farpointedata.com
Website: www.farpointedata.com

 **Farpointe Data**®
Readers © Credentials

P-400

125 kHz Proximity Card Reader

Pyramid Series Proximity®
Data Sheet

Features and Specifications:

Technology: Proximity	Frequency: 125 kHz
Mounting: Mullions, including metal door and window frames, as well as flat surfaces	Dimensions (HxWxD): 5.25 x 2 x 0.75 inches (134 x 51 x 19 mm)
OEM Label Area Dimensions: N/A	Weight: 18 oz. (510g)
Certifications: FCC, ICC, CE, C-Tick	IP Code: IP67 ⁴
Voltage²: +5 - 16 VDC	Current Draw: 30 mA typical, 75 mA peak @ 12VDC
Read Range³: Up to 1 inch (25 mm)	Cabling⁵: 24 AWG minimum, multi-conductor stranded with an overall foil shield
Interface: Wiegand ABA Track II	Operating Temperature: -40° F to 149° F (-40° C to +65° C)
Color Options: Stainless steel enclosure with anti-ballistic laminate face	Audio Tone: Beeper included standard
Indoor & Outdoor Installation: Electronics sealed in weather- and tamper-resistant epoxy potting	Warranty: Limited lifetime warranty
LED: N/A	Keypad Output⁶: N/A
Technologies Supported: P-400: Pyramid Series Proximity Cards and Tags ⁷ P-400-H: Pyramid + certain HID® Proximity protocols ⁸ P-400-A: Pyramid + certain AWID® 125-kHz Proximity protocols ⁹ P-400-H-A: Pyramid + certain HID 125-kHz Proximity protocols + certain AWID 125-kHz Proximity protocols	

² Linear power supplies are recommended for best operation.

³ Using PSC-1 Standard Light Proximity Card with 12VDC at the reader.

⁴ Self evaluated

⁵ For example Belden 9535 or similar.

⁶ Available only on P-640 models; 8-Bit Burst or 26-bit Wiegand standard, for 4-Bit Burst and other options please contact Farpointe.

⁷ Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.

⁸ Examples may include, and may not be limited to, ProxCard® II, ISOProx® II and ProxKey® II.

⁹ Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card and KT Key Tag.

Farpointe Data reserves the right to change specifications without notice.

260 North Wolfe Road
Sunnyvale, CA 94085 USA
Tel: +1-408-731-8700
Email: support@farpointedata.com
Website: www.farpointedata.com


Readers  Credentials