

# HID Prox 125 kHz Proximity – Credentials



**ProxCard® II**    **ISOProx® II**    **DuoProx® II**    **Smart ISOProx II™**    **Smart DuoProx® II**    **iCLASS® Prox**    **FlexSmart® MIFARE®/ Prox**    **ProxCard® Plus**    **ProxKey® II**    **MicroProx® Tag**    **ProxPass® II**

Base Part Number	1326	1386	1336	1397	1398	202X; 203X	1431	16-9	1346	1391	1351	
<b>Read Range: *</b>												
<b>ProxPoint® Plus</b>	Up to 3.0" (7.6 cm)			Up to 2.5" (6.35 cm)				Up to 1.0" (2.5 cm)		Up to 1.5" (3.8 cm)	Up to 2.0" (5.1 cm)	N/A
<b>MiniProx®</b>	Up to 5.5" (14.0 cm)			Up to 5.0" (12.7 cm)				Up to 2.0" (5.1 cm)		Up to 2.5" (6.4 cm)		N/A
<b>Thinline® II</b>	Up to 5.5" (14.0 cm)			Up to 5.0" (12.7 cm)				Up to 1.5" (3.8 cm)	Up to 2.0" (5.1 cm)	Up to 3.0" (7.6 cm)		N/A
<b>ProxPro®</b>	Up to 8.0" (20.3 cm)			Up to 7.0" (17.8 cm)				Up to 3.0" (7.6 cm)		Up to 4.0" (10.2 cm)		N/A
<b>ProxPro® II</b>	Up to 9.0" (22.9 cm)			Up to 8.0" (20 cm)				Up to 4.0" (10.2 cm)		Up to 4.5" (11.4 cm)		N/A
<b>MaxiProx®</b>	Up to 29" (73.7 cm)			Up to 20" (50.8 cm)				Up to 13.0" (33 cm)	Up to 17.0" (43.2 cm)	Up to 15.0" (38 cm)	Up to 8' (2.5 m)	
<b>EntryProx™</b>	Up to 3.0" (7.6 cm)			Up to 2.5" (6.35 cm)				Up to 1.0" (2.5 cm)	Up to 1.5" (3.8 cm)	Up to 2.0" (5.1 cm)	N/A	
<b>Prox80™</b>	Up to 5.5" (14 cm)	Up to 5" (12.5 cm)		Up to 2.5" (6.2 cm)		Up to 5" (12.5 cm)		Up to 1.5" (3.7 cm)	Up to 2" (5 cm)	Up to 2.5" (6.2 cm)	N/A	
<b>Memory Size/ Application Area</b>	N/A					2k bits with 2 application areas; 16k bits with 2 application areas, 16k bits with 16 application areas; 32k bits (16k/2+16k/1), 32k bits (16k/16+16k/1)	MIFARE 1K: 1K byte (8,192 bits) in 16 64-byte Sectors  MIFARE 4K: 4K byte (32,768 bits) in 40 Sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes.	N/A				
<b>HID Proximity 125 kHz</b>	Yes											
<b>Contact Smart Chip Module Embeddable</b>	No			Optional				No				
<b>Wiegand Strip</b>	No						Yes		No			
<b>Magnetic Stripe</b>	No	Yes	No	Yes	Optional							No
<b>Printable **</b>	Yes										No	
<b>Slot Punch</b>	Vertical (standard)	Horizontal or Vertical optional		Vertical optional				Horizontal or Vertical optional	Keyring	No		
<b>Visual Security Options</b>	N/A			Yes						N/A		
<b>Warranty</b>	Lifetime											

\* Dependent upon installation conditions.

\*\* Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.