

MTPX-MF-SA


STANDALONE MIFARE PROXIMITY READER

MTPX-MF-SA is an offline reader for access control. The Reader can be configured via USB connection or via card configuration. Issuing user cards is done by the software with the help of the desktop USB card reader. The access rights are written in the user card itself. The reader is compatible with our Access (PROA MS) and Hotel (PROH MS) softwares. The collecting of the past events can be also done by USB connection or by Event collect card.



FEATURES

Mounting:	Surface
Housing:	Moulded Aluminium/ABS
Reader type:	Mifare R/W
Cards supported:	Mifare Classic 1K, 4K
Read range:	Up to 6 cm
Operating frequency:	13.56 MHZ
User capacity:	Unlimited
Events memory:	3500 events
Relay activation time:	Pulse mode (1 to 255 s) or Toggle mode (ON/OFF)
Reader mode:	Sector read/write
Tamper protection:	Yes
Software support:	PROH-MS, PROA-MS
Event collection:	By Event Collect Card or via USB micro connector
Blacklist capacity:	500 cards
Data connectivity:	USB micro connector
Schedule activation:	4 definable actions of lock/unlock based on the time and day of the week
Firmware upgrade:	Yes, via USB
Configuration:	By software with USB connection or programming cards created using software and USB desktop reader
Credit on card:	Yes



SPECIFICATIONS

Electrical Characteristics:

Operating Voltage:	12V DC
Current consumption:	Maximum 150 mA
Data connectivity:	Micro USB connector for standard connection to PC
Output:	1 built-in relay (2A; 24V AC/DC), RS485 for remote relay unit
Inputs:	RU2, DINRTT, RTT
Tamper:	Push button
Signalization:	LED, buzzer


Environmental Characteristics:

IP rating:	IP65
Operating Temperatures:	-20°C to +50°C (non-condensing)

Mechanical Characteristics:

Dimensions (mm)	51 L x 92 H x 25 W
-----------------	--------------------

DIMENSIONS



COLOURS




READER CONFIGURATION

WITH USB



WITH CARD




FOBS & CARDS


Ref.	PBX-1E-MS50	PBX-2-MS50	PBX-2C-MS50	PBX-2-MS70
Features	ABS Waterdrop keyfob - MS 50 NXP Mifare - 1K Memory	0.75mm ISO Card - NXP Mifare S50 - 1K memory	2mm NISO Card - NXP Mifare S50 - 1K Memory	0.75mm ISO Card - NXP Mifare S70 - 4K Memory

PROA-MS (ACCESS SOFTWARE)

- Management of unlimited number of separate sites
- 80 Doors(Readers) per site, unlimited number of users per site
- Unlimited access levels
- User cards programming with PROX-USB Desktop Reader
- MS Access Database
- Reports for Events, Cards, User List, System Logs
- Configuring the reader by USB connection or by creating the Setup card
- Download reader events by USB connection or card
- Operating System: Windows 7, 8, 10
- Compatible hardware:
 - PROX-USB desktop card Reader/Writer
 - HL1000-MF Hotel lock
 - DINMTPX-MF-SA standalone reader
- Multilanguage UK, FR, IT, ES, NL, DE.



ACCESS SOLUTIONS SYSTEM > READER ONLY



ACCESS SOLUTIONS SYSTEM > READER + REMOTE RELAY UNIT

